

# DUAL OUTPUT ADJUSTABLE DC POWER SUPPLY

M10-QD SERIES



NEW

## Features

- **Output off function**
- **Dual independent adjustable DC outputs.**
- Independent, series and parallel variety output
- Constant voltage and constant current
- Low ripple and noise
- Four LED displays with 3 digits, selectable for two sets output voltage and current display simultaneously
- 16 hours continuous output with full load
- Auto tracking output



M10-QD305

## Specifications

- .Line regulation: CV  $1 \times 10^{-4} + 3\text{mV}$  CC  $2 \times 10^{-3} + 3\text{mA}$
- .Load regulation: CV  $1 \times 10^{-4} + 4\text{mV}$  CC  $2 \times 10^{-3} + 5\text{mA}$
- .Ripple & noise: CV 1mV rms CC 3mA rms
- .Display accuracy:  $\pm 0.5\% \text{Rdg} + 2\text{digits}$
- .Input voltage: 110~127VAC  $\pm 10\%$ , 220~240  $\pm 10\%$  Switchable

Model	Independent Output	Series Output	Parallel Output	Dimensions (W×H×D)	Weight (kg)
M10-QD302	CH1 0~30V/0~2A CH2 0~30V/0~2A	CH1+CH2 0~60V/0~2A	CH1//CH2 0~30V/0~4A	250×135×300 mm	7.8
M10-QD303	CH1 0~30V/0~3A CH2 0~30V/0~3A	CH1+CH2 0~60V/0~3A	CH1//CH2 0~30V/0~6A	250×135×300 mm	7.8
M10-QD305	CH1 0~30V/0~5A CH2 0~30V/0~5A	CH1+CH2 0~60V/0~5A	CH1//CH2 0~30V/0~10A	250×135×300 mm	7.8
M10-QD3010	CH1 0~30V/0~10A CH2 0~30V/0~10A	CH1+CH2 0~60V/0~10A	CH1//CH2 0~30V/0~20A	250×135×460 mm	12
M10-QD3020	CH1 0~30V/0~20A CH2 0~30V/0~20A	CH1+CH2 0~60V/0~20A	CH1//CH2 0~30V/0~40A	250×135×460 mm	16
M10-QD6010	CH1 0~60V/0~10A CH2 0~60V/0~10A	CH1+CH2 0~120V/0~10A	CH1//CH2 0~60V/0~20A	250×135×460 mm	16

POWER SUPPLY

TEST INSTRUMENT

EDU. INSTRUMENT

METER

ACCESSORY