

## Product Specification

### MT-3202



|                       |                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------|
| Display               | 3 3/4                                                                                          |
| DCV                   | 400mV/4V/40V/400V/600V± (0.8%+5d)                                                              |
| ACV                   | 4V/40V/400V/600V± (1.2%+5d); True RMS                                                          |
| ACA                   | 4A± (3%+5d); 40A/400A/600A± (2%+5d); True RMS                                                  |
| Resistance (Ω)        | 400/4K/40K/400K/4M/40MΩ± (1.2%+5d)                                                             |
| Capacitance           | 4nF± (3%+15d);<br>40nF/400nF/4μF/40μF/400μF/4mF± (3%+5d)                                       |
| Temperature °C/<br>°F | -20°C~1000°C± (3%+5d); -4°F~1832°F± (3%+5d)                                                    |
| Frequency (Hz)        | (V) 4Hz / 40Hz / 400Hz / 4kHz / 40KHz<br>±(0.5%+5d),<br><br>(A) 40Hz / 400Hz / 1KHz ±(0.5%+5d) |
| NCV                   | Y                                                                                              |
| LED                   | Y                                                                                              |

|           |             |
|-----------|-------------|
| Battery   | 1.5V AAA*2  |
| Dimension | 190*71*30mm |