

UNI-T

Your Testing Specialist!

UTP3704S DC Power Supply

Model		UTP3704S
Basic Function		Range
Output Voltage	I, II III	0 ~ 32V 5V
Output Current	I, II III	0 ~ 3A 2A
Load Effect		CV ≤ 1 x 10 ⁻⁴ +2mV, CC ≤ 2mA
Output Adjustment Resolution		CV.....20mV(Typical Value), CC.....50mV(Typical Value)
Mutual Effect		CV.....5X10 ⁻⁵ +1mV , CC.....<0.5mA
Tracking Error		5X10 ⁻³ +2mV
Indication Method		Digital Display. Voltage and current are simultaneously displayed
Feature		Steady voltage and steady current can be auto switched. Protection method of current limitation is adopted.
III		Output Voltage : 5V , Output Current : 0 ~ 2A , Ripple and Noise : <3mV.
Reliability		MTBF (e) : ≥2000h
Other Function		I way and II way can be master-slave tracking and cascade use.
General Feature		
Power		220V±10% , 50Hz±4%
Operation Environment		Operation Temperature:0°C ~ +40°C , storage
Product Color		Ivory White+Grey
Product Net Weight		4 kg (about)
Product Size		290mm×158mm×213mm
Standard Accessories		Power Line
Standard Packing		Carton, Manual, Warranty