



UT251 SERIES

High Sensitivity Leakage Current Clamp Meters

UT251A • UT251B • UT251C



IEC:1010-1

IEC:1010-2-032

NEW



■ UT251A



■ UT251B



■ UT251C

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT251A	UT251B	UT251C
Model				
Leakage Current(A)	0.001mA~60.00A	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
	60.00A~199.9A		±(2%+5)	±(2%+5)
	200.0A~300.0A		±(4%+5)	±(3%+5)
	300.0A~600.0A			±(4%+5)
Voltage(Freq.)	0V~600V (50Hz/60Hz)	✓	✓	✓
Resolution		1uA	10uA	0.1mA
Features				
Display Type	4 Digits Display LCD	✓	✓	✓
Auto Range		✓	✓	✓
Clamp Size		25mm×30mm	35mm×40mm	35mm×40mm
RS-232		✓	✓	✓
Data Logging		99	99	99
Peak Value		✓	✓	✓
Data Hold		✓	✓	✓
Auto Power Off	Around 5 Minutes	✓	✓	✓
Low Battery Indication	≤7.2V	✓	✓	✓
Over-Range Display	OL	✓	✓	✓
Test Mode	Clamp CT, Integral Approach	✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	32mm × 15mm
Product Color	Red and Grey
Product Net Weight	120g
Product Size	175mm × 70mm × 38mm
Standard Accessories	Battery,RS-232 Interface Cable,PC Software CD,Tool Box
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	6PCs
Standard Carton Measurement	591mm × 370mm ×474mm (0.104CBM Per Standard Carton)
Standard Carton Gross Weight	24Kg